



HCM

SKID STEER DRILLS



TEI ROCK DRILLS

PO BOX 1309, MONTROSE, CO 81402

(800) 777-3745 • (970) 249-1515 • www.teirockdrills.com



HCM DRILLING IN A QUARRY

HCM DRILL TOOL WITH HCF6 FEED

	U.S.	Metric
HCM350 System Flow and Pressure	35 GPM @ 2250 PSI	132 LPM @ 155 BAR
HCM350R System Flow and Pressure	25 GPM @ 3000 PSI	95 LPM @ 207 BAR
HCM350 Hole Size	1.375" to 3.0"	35mm to 76mm
HCM350R Hole Size	2.75" to 8.0"	70mm to 203mm
HCF6 Drill Length	9.8 feet	3.0 meters
HCF6 Travel	6.0 feet	1.83 meters
HCF6 Pullback	4900 lbs.	2222 kgs.
Approximate Drill Tool Weight	2200 lbs.	997 kgs.

Standard Equipment:

- 360 Degree Positioning
- Patented Drill Feed System
- Single Hydraulic Clamp

Optional Equipment:

- Misting System for dust suppression
- Double Clamps
- Radio/Cable Controls

ALL ATTACHMENT CARRIERS MUST BE PLUMBED WITH LOW PRESSURE RETURN AUXILIARY HYDRAULICS. AN ADDITIONAL HYDRAULIC OIL COOLER IS RECOMMENDED FOR PRODUCTION DRILLING. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



HCM WITH RADIO CONTROLS

The **HCM Skid Steer** series of drills from TEI makes use of this fine tool carrier. Taking advantage of the universal mounting plate the HCM drill can be changed with a bucket in minutes. The wide range of rotary top drives and drifters available makes the skid steer an excellent drilling platform. Hole sizes vary from 1-1/2 to 8 inches with depths up to 200 feet. HCM drills come with 360 degree positioner and a 2 foot crowd cylinder, making it possible to drill at any angle. Please talk to a TEI sales representative to get the correct match for your skid steer to a drilling attachment.



HCM INSTALLING MICROPILES



HCM CONTROL PANEL



HCM-GEO 200 FT HOLES



INSTALLING 6" TIE-BACKS



HCM DETACHED FROM SKID STEER