



# HEM-40ED

## SOIL NAILING DRILL



**TEI ROCK DRILLS**

PO BOX 1309, MONTROSE, CO 81402

(800) 777-3745 • (970) 249-1515 • [www.teirockdrills.com](http://www.teirockdrills.com)



## **DRILL SPECIFICATIONS**

---

- 40' drill travel with 5' crowd cylinder
- Maximum allowable torque is 5,000 ft/lbs
- Pullback is either 9,000 lbs. or 12,000 lbs.
- Approximate drill tool weight 6,000 lbs.
- For use on minimum 20 ton or larger excavator
- Radio Controls Standard
- Machine must be plumbed with auxillary hammer hydraulics

**ALL ATTACHMENT CARRIERS MUST BE PLUMBED WITH LOW PRESSURE RETURN AUXILIARY HYDRAULICS. AN ADDITIONAL HYDRAULIC OIL COOLER IS RECOMMENDED FOR PRODUCTION DRILLING. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.**

The **HEM-40ED** is a drill designed to install soil nails and tiebacks in a single-pass. The 40' drill stroke allows for rapid installation, smaller crews and quick movement between holes. There are many different hydraulic rotary heads and drifters available for mounting on the HEM-40ED to solve most drilling applications.



**HEM-40HD**

